

Lift and Transport Truck HTW 50/100 Standard Model



The lift and transport truck has a rugged, torsion-resistant frame structure and is made of powder coated steel (grey – RAL 9007). Additionally it has a smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling and 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, $d = 125$ mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 750 x 320 mm
Dimensions highest Position W/D/H:	2150 x 750 x 1650 mm
Carrying capacity:	max. 250 kg
Dead weight:	approx. 100 kg
Material:	Steel
Colour:	Light grey RAL 9007 (powder coated)
Type:	HTW 50/100
Article No.:	050.010.010

Lift and Transport Truck HTW 50/100 – 350 kg

Material: Steel Article-No.: 050.010.012

Additional models see back page

TekEquipment™

AU 1300 368 138

NZ 0800 456 217

tekequipment.com.au



KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



KUGEL
medical