Lift and Transport Truck HTW 50/010 Basic Model





The lift and transport truck has a rugged, torsion-resistant frame structure and is made of powder coated steel (grey – RAL 9007). Additionally, it has a smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling, 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, d = 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. A roller track comprising 4 carrying rollers, as well as a holding device for a body tray have been arranged on top of the truck. The slide handles of the lift and transport truck can be removed. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads.

Technical Data:

Dimensions lowest Position W/D/H: Dimensions highest Position W/D/H: Carrying capacity: Dead weight: Material: Colour: Type: Article No.: 2150 x 750 x 320 mm 2150 x 750 x 1650 mm max. 250 kg approx. 100 kg Steel Light grey RAL 9007 (powder coated) HTW 50/010 050.010.650

TekEquipment[®]

Ph: 1300 368 138 www.tekequipment.com.au info@tekequipment.com.au



Ph: 0800 456 217 info@tekmed.co.nz www.tekmed.co.nz

KUGEL medical GmbH & Co. KG Hermann-Köhl-Str. 2A DE - 93049 Regensburg/Germany Phone +49/941/20 86 48-0 Fax +49/941/20 86 48-29 www.KUGEL-medical.de





Subject to technical modifications as required by products improvements (Version 01/2017)