

Monoblock Refrigerator System KT 80 Ceiling Design



Connector-ready cooling units, which is ready for immediate use. Mounted directly on top of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation and a digital temperature indicator with connection and protective plug.

Refrigerant: R 404A

Ambient temperature +5 °C up to +45 °C

Technical data:

Temperature range:	+10 °C to -5 °C
Voltage:	230 V / 1 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	860 Watt
Rated Input (when normally running):	600 Watt
Rated Input:	3,5 Amp
Peak current:	15 Amp
Max current:	4,6 Amp
Defrost:	Hot gas defrosting
Weight:	42 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	400 Watt
<u>Condenser:</u>	
Air flow:	400 m ³ /h
<u>Evaporator:</u>	
Air flow:	500 m ³ /h
Air throw:	3 m (Standard)
Dimensions W/D/H:	430 x 771 x 378 mm
Dimensions Opening L/W:	355 x 306 mm
Type:	KT 80
Article-No.:	040.100.010

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de



KUGEL
medical
■ ■ ■ ■